

FUSION 3 Extrusion Welder



Easy operation due to its ergonomic, slim line design. The FUSION 3's long and narrow shape makes it ideal for welding on the ground from a standing position.

Benefits

- Suitable for PP, HDPE, and LDPE
- Ergonomic and easy to use
- Extensively field tested
- Continuous, independent adjustment of the air temperature and plast output rate possible
- Motor start-up protection prevents damage from cold starts
- 360° adjustable welding shoe
- Grip can be mounted in two positions (L or R)
- Twist-free welding rod intake on left and right side of tool

Why Buy From Us

The FUSION 3 is available in Canada only through STANMECH and its distributor network. We offer same-day shipping and we service everything we sell from our facility in Burlington, Ontario, Canada.

Technical Data – FUSION 3

Voltage	V~	230
Power consumption	W	3500
Frequency	Hz	50 / 60
Welding rod	mm	Ø 3 – 4 / Ø 4 – 5
Output	kg/h	PE: 2.0 – 3.6 PP: 1.8 – 3.4
Air temperature	°C	max. 350
Plast. temperature	°C	max. 320
Size (L x W x H)	mm	670 x 90 x 180
Weight	kg	7.2 (with cord)
Approval markings		CE, S+, QPS
Electrical protection		Class II