

*MACHINE SPECIFICATIONS

PACKAGE SIZE RANGE						
Model	Length		Width		Height	
	Max	Min	Max	Min	Max	Min
SA	12"	3 1/2"	8"	2"	4 1/2"	1"
SA-2	20"	5 1/2"	14"	4"	12 "	2"

FILM ROLL CAPACITY						
Model	Roll Width		Roll Diameter	Core Diameter	Film Cutoff	
	Max	Min	Max	Std.	Max	Min
SA	18"	3-1/4"	12"	3"	-"	6 1/4"
SA-2	28"	3-1/4"	12"	3"	-"	8 1/4"

MACHINE SPECIFICATIONS						
Model	Length	Width	Height	Weight	Electrics	
SA	~4'	~2'6"	~16"	Under 100	110/1/60 – 20 AMP	
SA-2	~6'	~4'	~16"	Under 100	110/1/60 – 20 AMP	

* All specifications preliminary and subject to change. Maximum product speed range will vary depending on overall package dimensions and the film type selected.

Machine Dimensions:	2 side by side table top size machines
Max Stroke Speed:	targeted at 8-15 strokes per minute on tuck/fold station
Standard Electrical:	110V/1Ph/60Hz, 20 AMP
Air Requirements:	Std. shop air or small air compressor
Operating Modes:	Manual / Auto
Safety:	Guarding, awareness barriers, E-Stop, Dual Palm button advancement and Industry standard warning labels are clearly visible.

STANDARD FEATURES:

- 2 side-by-side stations— 1) Wrap/Cut/Seal and 1)Tuck/Fold/Seal
- Standard heaters for the sealing of pre-treated (glued) paper or clear BOPP film
- “Quick Change” Size Part Components for 5minute changeovers
- Bottom seam or Side long seam operation
- Convenient digital heater temperature controls
- Teflon coated surfaces and folding line
- Operator Control with Manual, Auto, Reset functions, E-stop and warning lights
- Quick change film spindle which fits commercially available BOPP or gift wrap paper
- Integrated dual direction knife and long seam heater bar
- Adjustable, reciprocating side heaters
- Guarded heat points and pinch point warnings
- Fully synchronized product advancement and film sealing
- Allen Bradley—PLC and stepper motor for Programmable, self advancing film assist
- Film cut length and product location gauging
- Clamp/cut/seal assist for tack/bottom seal operation
- Double advancing pusher head for “product push” advancement
- Reciprocating/Time out Heater mounts
- Product Path clearing baton
- Installation, operation instructions