



HEMTEK K-ST Stationary Hot Air Welder

The HEMTEK K-ST is intuitive to set-up and use. Easy to mount to almost any work surface – use while sitting or standing. The HEMTEK K-ST makes keder creation easy. Lug width infinitely adjustable, piping diameter from 3-13 mm.

- Drive speed of up to 12 m per minute
- Weld width of 8 mm
- Flag width adjustable up to 80 mm
- Keder rope diameter from 3-13 mm
- Adjustable speed, temperature, and pressure
- Simple controls, easy to use
- Can be mounted onto almost any table - use sitting or standing
- Tool-free adjustment of guide
- Foot pedal starts/stops welding process leaving both hands free to guide material
- Easy to use cool-down mode prolongs element life

Technical Data

Voltage	V	120	230
Power consumption	W	1800	2350
Temperature	°C	100 - 650	100 - 650
Drive speed	m/min.	0.8 - 12	0.8 - 12
Welding seam width	mm	8	8
Noise level	dB	70	70
Size (L x W x H)	mm	433 x 350 x 600	433 x 350 x 600
Weight	kg	27	27
Approval markings		CE, QPS	CE, QPS
Electrical protection		Class I	Class I

Article No.:

162.605: HEMTEK K-ST 120 V / 1800 W, with plug

162.499: HEMTEK K-ST 230 V / 2350 W, without plug

Included in delivery: HEMTEK K-ST, table clamp, flap piping guide



HEMTEK K-ST Accessories



161.259: Flap piping welding nozzle 8 mm



162.379: Pressure roller 8 mm, top



161.202: Pressure roller 40 mm, bottom



160.749: Double flap-piping guide



163.798: Nozzle adjustment gauge



163.796: Conversion kit from HEMTEK ST to HEMTEK K-ST